

Description

Fastener part number

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS90354S0511 |
| Minimum Qty (MOQ): | 10 EA |
| NSN: | 5320-00-171-6081 |
| Schedule B: | 7318.15.2091 |
| ECCN: | 9A991 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |



* See page 2 for technical characteristics

P/N MS90354S0511 Specifications

| | |
|--|---|
| Fastener Length: | 0.842 Inches Maximum |
| Head Style: | Straight Pan |
| Head Height: | 0.062 Inches Minimum And 0.070 Inches Maximum |
| Shank Diameter: | 0.162 Inches Minimum And 0.164 Inches Maximum |
| Shank Style: | Self-plugging Mechanically Locked Stem |
| Head Major Diameter: | 0.250 Inches Minimum And 0.272 Inches Maximum |
| Expansion Device: | Serrated Stem-type W |
| Grip Length: | 0.656 Inches Minimum And 0.720 Inches Maximum |
| Minimum Tensile Strength: | 112000 Pounds Per Square Inch |
| Hardness Rating: | 48.0 Rockwell C Minimum Stem And 53.0 Rockwell C Maximum Stem |
| Hardness Rating: | 48.0 Rockwell C Minimum And 53.0 Rockwell C Maximum Stem |
| Shear Strength: | 2340 Single Pounds Per Square Inch |
| Material: | Steel Comp 4027 Sleeve Or Steel Comp 4037 Sleeve Or Steel Comp 4130 Sleeve |
| Material: | Steel Comp 8740 Stem |
| Material: | Steel Comp 4027 Or Steel Comp 4037 Or Steel Comp 4130 Sleeve |
| Material Document And Classification: | 66 Fed Std All Material Responses Sleeve Or Astm A547 Assn Std 2nd Material Response Sleeve Or Mil-s-6758 Mil Spec 3rd Material Response Sleeve |
| Material Document And Classification: | Astm A547 Assn Std Single Material Response Stem Or Mil-s-6049 Mil Spec Single Material Response Stem |
| Material Document And Classification: | 66 Fed Std All Material Responses Or Astm A547 Assn Std 2nd Material Response Or Mil-s-6758 Mil Spec 3rd Material Response Sleeve |
| Material Document And Classification: | Astm A547 Assn Std Single Material Response Or Mil-s-6049 Mil Spec Single Material Response Stem |
| Surface Treatment: | Cadmium Sleeve And Chromate Sleeve |
| Surface Treatment: | Cadmium Stem |
| Surface Treatment: | Cadmium And Chromate Sleeve |
| Surface Treatment Document And Classification: | Qq-p-416,ty 1,cl 3 Fed Spec Single Treatment Response Stem |

How to Order

Order this fastener from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS90354S0511> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.