

**Description**

blind rivet part number

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | MS90354S0604                                |
| Minimum Qty (MOQ):      | 10  |
| NSN:                    | 5320-00-160-3215                            |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |



\* See page 2 for technical characteristics

# P/N MS90354S0604 Specifications

|  |   |
|--|---|
| Fastener Length:                               | 0.428 Inches Maximum  |
| Head Style:                                    | Straight Pan  |
| Head Height:                                   | 0.125 Inches Minimum And 0.135 Inches Maximum   |
| Shank Diameter:                                | 0.197 Inches Minimum And 0.199 Inches Maximum   |
| Shank Style:                                   | Self-plugging Mechanically Locked Stem  |
| Head Major Diameter:                           | 0.305 Inches Minimum And 0.332 Inches Maximum   |
| Expansion Device:                              | Serrated Stem-type W  |
| Grip Length:                                   | 0.219 Inches Minimum And 0.282 Inches Maximum   |
| Minimum Tensile Strength:                      | 112000 Pounds Per Square Inch   |
| Hardness Rating:                               | 48.0 Rockwell C Minimum Stem And 53.0 Rockwell C Maximum Stem   |
| Hardness Rating:                               | 48.0 Rockwell C Minimum And 53.0 Rockwell C Maximum Stem  |
| Shear Strength:                                | 3450 Single Pounds Per Square Inch  |
| Material:                                      | Steel Comp 4027 Sleeve Or Steel Comp 4037 Sleeve Or Steel Comp 4130 Sleeve  |
| Material:                                      | Steel Comp 8740 Stem  |
| Material:                                      | Steel Comp 4027 Or Steel Comp 4037 Or Steel Comp 4130 Sleeve  |
| Material Document And Classification:          | 66 Fed Std 1st Material Response Sleeve Or Astm A547 Assn Std 2nd Material Response Sleeve Or 66 Fed Std 3rd Material Response Sleeve Or Mil-s-6758 Mil Spec 3rd Material Response Sleeve |
| Material Document And Classification:          | Mil-s-6049 Mil Spec Single Material Response Stem Or Astm A547 Assn Std Single Material Response Stem   |
| Material Document And Classification:          | Mil-s-6049 Mil Spec Single Material Response Or Astm A547 Assn Std Single Material Response Stem  |
| Material Document And Classification:          | 66 Fed Std 1st Material Response Or Astm A547 Assn Std 2nd Material Response Or 66 Fed Std 3rd Material Response Or Mil-s-6758 Mil Spec 3rd Material Response Sleeve                      |
| Surface Treatment:                             | Cadmium Sleeve And Chromate Sleeve  |
| Surface Treatment:                             | Cadmium Stem  |
| Surface Treatment:                             | Cadmium And Chromate Sleeve   |
| Surface Treatment Document And Classification: | Qq-p-416,ty 1,cl 3 Fed Spec Single Treatment Response Stem  |

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS90354S0604> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.