

## P/N MS90354S0607

### **Description**

MS90354S0607 Rivet

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: MS90354S0607

Minimum Qty (MOQ): 10

NSN: 5320-00-156-4566

ECCN: EAR99

National Motor Freight: 106510, Rivets I / S Plain / Galvanized Etc









# P/N MS90354S0607 Specifications

| Fastener Length:                               | 0.616 Inches Maximum  |
|--|---|
| Head Style:                                    | Straight Pan  |
| Head Height:                                   | 0.125 Inches Minimum And 0.135 Inches Maximum   |
| Shank Diameter:                                | 0.197 Inches Minimum And 0.199 Inches Maximum   |
| Shank Style:                                   | Self-plugging Mechanically Locked Stem  |
| Head Major Diameter:                           | 0.305 Inches Minimum And 0.332 Inches Maximum   |
| Expansion Device:                              | Serrated Stem-type W  |
| Grip Length:                                   | 0.406 Inches Minimum And 0.470 Inches Maximum   |
| Minimum Tensile Strength:                      | 112000 Pounds Per Square Inch   |
| Hardness Rating:                               | 32.0 Rockwell C Minimum Body And 40.0 Rockwell C Maximum Body                                       |
| Hardness Rating:                               | 48.0 Rockwell C Minimum Stem And 53.0 Rockwell C Maximum Stem                                       |
| Hardness Rating:                               | 32.0 Rockwell C Minimum And 40.0 Rockwell C Maximum Body  |
| Hardness Rating:                               | 48.0 Rockwell C Minimum And 53.0 Rockwell C Maximum Stem  |
| Shear Strength:                                | 3450 Single Pounds Per Square Inch  |
| Material:                                      | Steel Comp 4037 Sleeve Or Steel Comp 4130 Sleeve  |
| Material:                                      | Steel Comp 8740 Stem  |
| Material:                                      | Steel Comp 4037 Or Steel Comp 4130 Sleeve   |
| Material Document And Classification:          | Mil-s-6758 Mil Spec 1st Material Response Sleeve Or Astm A547 Assn Std 2nd Material Response Sleeve |
| Material Document And Classification:          | Mil-s-6049 Mil Spec 1st Material Response Stem Or Astm A547 Assn Std 2nd Material Response Stem     |
| Material Document And Classification:          | Mil-s-6049 Mil Spec 1st Material Response Or Astm A547 Assn Std 2nd Material Response Stem          |
| Material Document And Classification:          | Mil-s-6758 Mil Spec 1st Material Response Or Astm A547 Assn Std 2nd Material Response Sleeve        |
| Surface Treatment:                             | Cadmium Sleeve Or Chromium Sleeve   |
| Surface Treatment:                             | Cadmium Stem  |
| Surface Treatment:                             | Cadmium Or Chromium Sleeve  |
| Surface Treatment Document And Classification: | Qq-p-416,ty 1 Or 2,cl 3 Fed Spec Single Treatment Response Stem                                     |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Sleeve  |

## **How to Order**

Order this blind rivet from our inventory online by visiting <a href="https://military-fasteners.com/rivets/blind+rivets/MS90354S0607">https://military-fasteners.com/rivets/blind+rivets/MS90354S0607</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.