

Description

Fastener part number

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS90354S0610
Minimum Qty (MOQ):	10 EA
NSN:	5320-00-156-4569
Schedule B:	7318.15.2010
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS90354S0610 Specifications

Fastener Length:	0.803 Inches Maximum
Head Style:	Straight Pan
Head Height:	0.125 Inches Minimum And 0.135 Inches Maximum
Shank Diameter:	0.197 Inches Minimum And 0.199 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.305 Inches Minimum And 0.332 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.594 Inches Minimum And 0.657 Inches Maximum
Minimum Tensile Strength:	112000 Pounds Per Square Inch
Hardness Rating:	32.0 Rockwell C Minimum Body And 40.0 Rockwell C Maximum Body
Hardness Rating:	48.0 Rockwell C Minimum Stem And 53.0 Rockwell C Maximum Stem
Hardness Rating:	32.0 Rockwell C Minimum And 40.0 Rockwell C Maximum Body
Hardness Rating:	48.0 Rockwell C Minimum And 53.0 Rockwell C Maximum Stem
Shear Strength:	3450 Single Pounds Per Square Inch
Material:	Steel Comp 4037 Sleeve Or Steel Comp 4130 Sleeve
Material:	Steel Comp 8740 Stem
Material:	Steel Comp 4037 Or Steel Comp 4130 Sleeve
Material Document And Classification:	Mil-s-6758 Mil Spec 1st Material Response Sleeve Or Astm A5,47 Assn Std 2nd Material Response Sleeve
Material Document And Classification:	Mil-s-6049 Mil Spec 1st Material Response Stem Or Astm A547 Assn Std 2nd Material Response Stem
Material Document And Classification:	Mil-s-6049 Mil Spec 1st Material Response Or Astm A547 Assn Std 2nd Material Response Stem
Material Document And Classification:	Mil-s-6758 Mil Spec 1st Material Response Or Astm A5,47 Assn Std 2nd Material Response Sleeve
Surface Treatment:	Cadmium Sleeve Or Chromium Sleeve
Surface Treatment:	Cadmium Stem
Surface Treatment:	Cadmium Or Chromium Sleeve
Surface Treatment Document And Classification:	Qq-p-416,ty 1 Or 2,cl 3 Fed Spec Single Treatment Response Stem
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Sleeve

How to Order

Order this fastener from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS90354S0610> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.