

**Description**

Fastener part number

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS90354S0610
Minimum Qty (MOQ):	10 EA
NSN:	5320-00-156-4569
Schedule B:	7318.15.2010
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N MS90354S0610 Specifications

<b>Fastener Length:</b>	0.803 Inches Maximum
<b>Head Style:</b>	Straight Pan
<b>Head Height:</b>	0.125 Inches Minimum And 0.135 Inches Maximum
<b>Shank Diameter:</b>	0.197 Inches Minimum And 0.199 Inches Maximum
<b>Shank Style:</b>	Self-plugging Mechanically Locked Stem
<b>Head Major Diameter:</b>	0.305 Inches Minimum And 0.332 Inches Maximum
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Grip Length:</b>	0.594 Inches Minimum And 0.657 Inches Maximum
<b>Minimum Tensile Strength:</b>	112000 Pounds Per Square Inch
<b>Hardness Rating:</b>	32.0 Rockwell C Minimum Body And 40.0 Rockwell C Maximum Body
<b>Hardness Rating:</b>	48.0 Rockwell C Minimum Stem And 53.0 Rockwell C Maximum Stem
<b>Hardness Rating:</b>	32.0 Rockwell C Minimum And 40.0 Rockwell C Maximum Body
<b>Hardness Rating:</b>	48.0 Rockwell C Minimum And 53.0 Rockwell C Maximum Stem
<b>Shear Strength:</b>	3450 Single Pounds Per Square Inch
<b>Material:</b>	Steel Comp 4037 Sleeve Or Steel Comp 4130 Sleeve
<b>Material:</b>	Steel Comp 8740 Stem
<b>Material:</b>	Steel Comp 4037 Or Steel Comp 4130 Sleeve
<b>Material Document And Classification:</b>	Mil-s-6758 Mil Spec 1st Material Response Sleeve Or Astm A5,47 Assn Std 2nd Material Response Sleeve
<b>Material Document And Classification:</b>	Mil-s-6049 Mil Spec 1st Material Response Stem Or Astm A547 Assn Std 2nd Material Response Stem
<b>Material Document And Classification:</b>	Mil-s-6049 Mil Spec 1st Material Response Or Astm A547 Assn Std 2nd Material Response Stem
<b>Material Document And Classification:</b>	Mil-s-6758 Mil Spec 1st Material Response Or Astm A5,47 Assn Std 2nd Material Response Sleeve
<b>Surface Treatment:</b>	Cadmium Sleeve Or Chromium Sleeve
<b>Surface Treatment:</b>	Cadmium Stem
<b>Surface Treatment:</b>	Cadmium Or Chromium Sleeve
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 1 Or 2,cl 3 Fed Spec Single Treatment Response Stem
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Sleeve

## How to Order

Order this fastener from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS90354S0610> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.