

Description

Blind Rivet part number

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | MS90354U0506 |
| Minimum Qty (MOQ): | 20 |
| NSN: | 5320-01-204-4781 |
| ECCN: | EAR99 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |



P/N MS90354U0506 Specifications

| | |
|---|---|
| Fastener Length: | 0.530 Inches Maximum |
| Head Style: | Tapered Pan |
| Head Height: | 0.062 Inches Minimum And 0.070 Inches Maximum |
| Shank Diameter: | 0.162 Inches Minimum And 0.164 Inches Maximum |
| Shank Style: | Self-plugging Mechanically Locked Stem |
| Head Major Diameter: | 0.250 Inches Minimum And 0.272 Inches Maximum |
| Expansion Device: | Serrated Stem-type W |
| Grip Length: | 0.344 Inches Minimum And 0.407 Inches Maximum |
| Hardness Rating: | 326.0 Knoop Minimum Sleeve And 466.0 Knoop Maximum Sleeve |
| Hardness Rating: | 48.0 Rockwell C Minimum Stem And 53.0 Rockwell C Maximum Stem |
| Shear Strength: | 112000 Single Pounds Per Square Inch |
| Material: | Steel Overall |
| Material Document And Classification: | Astm A331 Assn Std Single Material Response Overall |
| Surface Treatment: | Cadmium Sleeve And Chromate Sleeve Or Aluminum Sleeve |
| Surface Treatment: | Cadmium Stem Or Aluminum Stem |
| Surface Treatment Document And Classification: | Qq-p-416 Ty 1 Cl 3 Fed Spec 1st Treatment Response Stem Or Mil-c-83488 Mil Spec 2nd Treatment Response Stem |
| Surface Treatment Document And Classification: | Qq-p-416 Ty 2 Cl 2 Fed Spec 1st Treatment Response Sleeve Or Mil-c-83488 Mil Spec 2nd Treatment Response Sleeve |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS90354U0506> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.