

Description

blind rivet part number

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS90354U0509
Minimum Qty (MOQ):	10
NSN:	5320-01-231-7532
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



NO IMAGE
AVAILABLE

P/N MS90354U0509 Specifications

Identification Code Color:	Green
Fastener Length:	0.717 Inches Maximum
Head Style:	Tapered Pan
Head Height:	0.062 Inches Minimum And 0.070 Inches Maximum
Shank Diameter:	0.162 Inches Minimum And 0.164 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.250 Inches Minimum And 0.272 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.531 Inches Minimum And 0.595 Inches Maximum
Hardness Rating:	326.0 Knoop Minimum Sleeve And 466.0 Knoop Maximum Sleeve
Hardness Rating:	48.0 Rockwell C Minimum Stem And 53.0 Rockwell C Maximum Stem
Shear Strength:	112000 Single Pounds Per Square Inch
Material:	Steel Comp 4027 Overall Or Steel Comp 4130 Overall Or Steel Comp 4140 Overall Or Steel Comp 4150 Overall Or Steel Comp 4620 Overall Or Steel Comp 4815 Overall Or Steel Comp 8615 Overall Or Steel Comp 8620 Overall Or Steel Comp 8630 Overall Or Steel Comp 8640 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Astm A331 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Sleeve And Chromate Sleeve
Surface Treatment:	Cadmium Stem
Surface Treatment Document And Classification:	Qq-p-416,ty1,c13 Fed Spec Single Treatment Response Stem
Surface Treatment Document And Classification:	Qq-p-416,ty2,c12 Fed Spec Single Treatment Response Sleeve

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS90354U0509> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.