

**Description**

High strength, protruding head, MS90354 series rivet

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | MS90354U0608                                |
| Minimum Qty (MOQ):      | 10  |
| NSN:                    | 5320-01-229-9628                            |
| Schedule B:             | 7318.15.2010                                |
| ECCN:                   | EAR99                                       |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |



\* See page 2 for technical characteristics

## P/N MS90354U0608 Specifications

|   |   |
|---|---|
| <b>Identification Code Color:</b>                     | Green   |
| <b>Fastener Length:</b>                               | 0.678 Inches Maximum  |
| <b>Head Style:</b>                                    | Tapered Pan   |
| <b>Head Height:</b>                                   | 0.125 Inches Minimum And 0.135 Inches Maximum                 |
| <b>Shank Diameter:</b>                                | 0.197 Inches Minimum And 0.199 Inches Maximum                 |
| <b>Shank Style:</b>                                   | Self-plugging Mechanically Locked Stem                        |
| <b>Head Major Diameter:</b>                           | 0.305 Inches Minimum And 0.332 Inches Maximum                 |
| <b>Expansion Device:</b>                              | Serrated Stem-type W  |
| <b>Grip Length:</b>                                   | 0.469 Inches Minimum And 0.532 Inches Maximum                 |
| <b>Hardness Rating:</b>                               | 326.0 Knoop Minimum Sleeve And 466.0 Knoop Maximum Sleeve     |
| <b>Hardness Rating:</b>                               | 48.0 Rockwell C Minimum Stem And 53.0 Rockwell C Maximum Stem |
| <b>Shear Strength:</b>                                | 112000 Single Pounds Per Square Inch                          |
| <b>Material:</b>                                      | Steel Overall   |
| <b>Material Document And Classification:</b>          | Astm A331 Assn Std Single Material Response Overall           |
| <b>Surface Treatment:</b>                             | Cadmium Sleeve And Chromate Sleeve                            |
| <b>Surface Treatment:</b>                             | Cadmium Stem  |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-416,ty1,cl3 Fed Spec Single Treatment Response Stem      |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-416,ty2,cl2 Fed Spec Single Treatment Response Sleeve    |

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS90354U0608> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.