

Description

Fastener Length: 5/8", MS90354 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS90354U0804
Minimum Qty (MOQ):	10
NSN:	5320-01-219-5432
Schedule B:	7326.90.8688
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N MS90354U0804 Specifications

Fastener Length:	0.648 Inches Maximum
Head Style:	Tapered Pan
Head Height:	0.400 Inches Minimum And 0.432 Inches Maximum
Shank Diameter:	0.258 Inches Minimum And 0.260 Inches Maximum
Head Major Diameter:	0.130 Inches Minimum And 0.140 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.219 Inches Minimum And 0.282 Inches Maximum
Hardness Rating:	326.0 Knoop Minimum Sleeve And 466.0 Knoop Maximum Sleeve
Hardness Rating:	48.0 Rockwell C Minimum Stem And 53.0 Rockwell C Maximum Stem
Material:	Steel Sleeve
Material:	Steel Stem
Material Document And Classification:	Astm A331 Assn Std Single Material Response Stem
Material Document And Classification:	Astm A331 Assn Std Single Material Response Sleeve
Surface Treatment:	Cadmium Sleeve And Chromate Sleeve Or Aluminum Alloy Sleeve
Surface Treatment:	Cadmium Stem Or Aluminum Alloy Stem
Surface Treatment Document And Classification:	Qq-p-416,ty 1 Cl 3 Fed Spec 1st Treatment Response Stem Or Mil-c-83488 Mil Spec 2nd Treatment Response Stem
Surface Treatment Document And Classification:	Qq-p-416,ty 2 Cl 2 Fed Spec 1st Treatment Response Sleeve Or Mil-c-83488 Mil Spec 2nd Treatment Response Sleeve

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS90354U0804> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.