

Description

Fastener Length: 1-1"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS90354U0805
Minimum Qty (MOQ):	10
NSN:	5320-01-195-3016
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



\* See page 2 for technical characteristics

# P/N MS90354U0805 Specifications

Fastener Length:	1.000 Inches Minimum
Head Style:	Straight Pan
Head Height:	0.130 Inches Minimum And 0.140 Inches Maximum
Shank Diameter:	0.258 Inches Minimum And 0.260 Inches Maximum
Head Major Diameter:	0.400 Inches Minimum And 0.432 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.281 Inches Minimum And 0.345 Inches Maximum
Minimum Tensile Strength:	3650 Pounds Per Square Inch
Hardness Rating:	48.0 Rockwell C Minimum Stem And 53.0 Rockwell C Maximum Stem
Shear Strength:	5900 Single Pounds Per Square Inch
Material:	Steel Comp 1010 Mechanical Lock Or Steel Comp 1020 Mechanical Lock Or Steel Comp 1144 Mechanical Lock Or Steel Comp 4037 Mechanical Lock Or Steel Comp 4130 Mechanical Lock Or Iron Alloy 660 Mechanical Lock Or Steel Comp 316 Mechanical Lock
Material:	Steel Comp 4027 Sleeve Or Steel Comp 4130 Sleeve
Material:	Steel Comp 8740 Stem
Material Document And Classification:	66 Fed Std 1st Material Response Mechanical Lock Or 66 Fed Std 2nd Material Response Mechanical Lock Or 66 Fed Std 3rd Material Response Mechanical Lock Or 66 Fed Std 4th Material Response Mechanical Lock Or 66 Fed Std 5th Material Response Mechanical Lock Or Ams5737 Assn Std 6th Material Response Mechanical Lock Or Ams5690 Assn Std 7th Material Response Mechanical Lock
Material Document And Classification:	Mil-s-6049 Mil Spec Single Material Response Stem Or Qq-w-405 Fed Spec Single Material Response Stem
Material Document And Classification:	Qq-w-405 Fed Spec 1st Material Response Sleeve Or Mil-s-6758 Mil Spec 2nd Material Response Sleeve
Surface Treatment:	Cadmium Mechanical Lock Or Passivate Mechanical Lock
Surface Treatment:	Cadmium Sleeve
Surface Treatment:	Cadmium Stem
Surface Treatment Document And Classification:	Qq-p-416,ty 1,cl 3 Fed Spec Single Treatment Response Stem
Surface Treatment Document And Classification:	Qq-p-416,ty 2 Fed Spec 1st Treatment Response Mechanical Lock Or Qq-p-35 Fed Spec 2nd Treatment Response Mechanical Lock
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Sleeve
Specification/standard Data:	96906-ms90354 Government Standard

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS90354U0805> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.