

Description

Fastener Length: 1"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | MS90354U0807 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5320-01-195-3017 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |

NO IMAGE
AVAILABLE

P/N MS90354U0807 Specifications

| | |
|---|--|
| Fastener Length: | 1.000 Inches Minimum |
| Head Style: | Straight Pan |
| Head Height: | 0.130 Inches Minimum And 0.140 Inches Maximum |
| Shank Diameter: | 0.258 Inches Minimum And 0.260 Inches Maximum |
| Head Major Diameter: | 0.400 Inches Minimum And 0.432 Inches Maximum |
| Expansion Device: | Serrated Stem-type W |
| Grip Length: | 0.406 Inches Minimum And 0.470 Inches Maximum |
| Minimum Tensile Strength: | 3650 Pounds Per Square Inch |
| Hardness Rating: | 48.0 Rockwell C Minimum Stem And 53.0 Rockwell C Maximum Stem |
| Shear Strength: | 5900 Single Pounds Per Square Inch |
| Material: | Steel Comp 1010 Mechanical Lock Or Steel Comp 1020 Mechanical Lock Or Steel Comp 1144 Mechanical Lock Or Steel Comp 4037 Mechanical Lock Or Steel Comp 4130 Mechanical Lock Or Iron Alloy 660 Mechanical Lock Or Steel Comp 316 Mechanical Lock |
| Material: | Steel Comp 4027 Sleeve Or Steel Comp 4130 Sleeve |
| Material: | Steel Comp 8740 Stem |
| Material Document And Classification: | 66 Fed Std 1st Material Response Mechanical Lock Or 66 Fed Std 2nd Material Response Mechanical Lock Or 66 Fed Std 3rd Material Response Mechanical Lock Or 66 Fed Std 4th Material Response Mechanical Lock Or 66 Fed Std 5th Material Response Mechanical Lock Or Ams5737 Assn Std 6th Material Response Mechanical Lock Or Ams5690 Assn Std 7th Material Response Mechanical Lock |
| Material Document And Classification: | Mil-s-6049 Mil Spec Single Material Response Stem Or Qq-w-405 Fed Spec Single Material Response Stem |
| Material Document And Classification: | Qq-w-405 Fed Spec 1st Material Response Sleeve Or Mil-s-6758 Mil Spec 2nd Material Response Sleeve |
| Surface Treatment: | Cadmium Mechanical Lock Or Passivate Mechanical Lock |
| Surface Treatment: | Cadmium Sleeve |
| Surface Treatment: | Cadmium Stem |
| Surface Treatment Document And Classification: | Qq-p-416,ty 1,cl 3 Fed Spec Single Treatment Response Stem |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2 Fed Spec 1st Treatment Response Mechanical Lock Or Qq-p-35 Fed Spec 2nd Treatment Response Mechanical Lock |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Sleeve |
| Specification/standard Data: | 96906-ms90354 Government Standard |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS90354U0807> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.