

Description

Fastener part number

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS90354U0817
Minimum Qty (MOQ):	5 EA
NSN:	5320-01-304-6084
Schedule B:	7318.15.2010
ECCN:	9A991
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE
AVAILABLE

P/N MS90354U0817 Specifications

Fastener Length:	1.281 Inches Maximum
Head Style:	Straight Pan
Head Height:	0.130 Inches Minimum And 0.140 Inches Maximum
Shank Diameter:	0.258 Inches Minimum And 0.260 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.400 Inches Minimum And 0.432 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	1.031 Inches Minimum And 1.095 Inches Maximum
Minimum Tensile Strength:	112000 Pounds Per Square Inch
Hardness Rating:	48.0 Rockwell C Minimum Stem And 53.0 Rockwell C Maximum Stem
Special Features:	No Lubrication,except Manufacturer's Option To Lubricate Lock Mechanism With Lox Compatibledry Film Lubricant; The "u" In The P/n Denotes Single Action Fasteners Installed With A Single Action Tool
Material:	Steel Comp E4340 Or Steel Comp 4027 Or Steel Comp 4037 Or Steel Comp 4130 Or Steel Comp 4140 Or Steel Comp 4150 Or Steel Comp 4340 Or Steel Comp 4620 Or Steel Comp 4815 Or Steel Comp 6150 Or Steel Comp 8615 Or Steel Comp 8620 Or Steel Comp 8630 Or Steel Comp 8640 Or Steel Comp 8740 Overall
Material Document And Classification:	Astma 331 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Sleeve And Chromate Sleeve Or Aluminum Alloy Sleeve
Surface Treatment Document And Classification:	Qq-p-416,ty 1,cl 3 Fed Spec Single Treatment Response Stem

How to Order

Order this fastener from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS90354U0817> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.