

Description

Fastener part number

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS90354U1004
Minimum Qty (MOQ):	5 EA
NSN:	5320-01-360-9176
Schedule B:	7318.15.2010
ECCN:	9A991
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed



NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS90354U1004 Specifications

Fastener Length:	0.508 Inches Nominal
Head Style:	Straight Pan
Head Height:	0.1310 Inches Minimum And 0.1410 Inches Maximum
Shank Diameter:	0.3100 Inches Minimum And 0.3120 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.4800 Inches Minimum And 0.5220 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.2190 Inches Minimum And 0.2820 Inches Maximum
Material:	Steel Comp E4340 Mechanical Locksteel Comp E4340 Sleeveiron Alloy 660 Stem

How to Order

Order this fastener from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS90354U1004> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.