

## P/N MS90354U1006

### **Description**

Fastener part number

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: MS90354U1006

Minimum Qty (MOQ): 5 EA

NSN: 5320-01-274-7295

Schedule B: 7318.15.2010

ECCN: 9A991

National Motor Freight: 106510, Rivets I / S Plain / Galvanized Etc



<sup>\*</sup> See page 2 for technical characteristics

# P/N MS90354U1006 Specifications

| Fastener Length:                               | 0.631 Inches Maximum  |
|--|---|
| Head Style:                                    | Straight Pan  |
| Head Height:                                   | 0.131 Inches Minimum And 0.141 Inches Maximum                 |
| Shank Diameter:                                | 0.310 Inches Minimum And 0.312 Inches Maximum                 |
| Shank Style:                                   | Self-plugging Mechanically Locked Stem                        |
| Head Major Diameter:                           | 0.480 Inches Minimum And 0.522 Inches Maximum                 |
| Expansion Device:                              | Serrated Stem-type W  |
| Grip Length:                                   | 0.344 Nominal Mils And 0.407 Nominal Centimeters              |
| Minimum Tensile Strength:                      | 112000 Pounds Per Square Inch                                 |
| Hardness Rating:                               | 326.0 Knoop Minimum Sleeve And 466.0 Knoop Maximum Sleeve     |
| Hardness Rating:                               | 48.0 Rockwell C Minimum Stem And 53.0 Rockwell C Maximum Stem |
| Special Features:                              | Single Action Fastener Installed With A Single Action Tool    |
| Material:                                      | Steel Sleeve  |
| Material:                                      | Steel Stem  |
| Material Document And Classification:          | Astm-a-331 Assn Std Single Material Response Sleeve           |
| Material Document And Classification:          | Astm-a-331 Assn Std Single Material Response Stem             |
| Surface Treatment:                             | Cadmium Sleeve And Chromate Sleeve                            |
| Surface Treatment:                             | Cadmium Stem  |
| Surface Treatment Document And Classification: | Qq-p-416,ty 1,cl 3 Fed Spec Single Treatment Response Stem    |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Sleeve  |
|  |   |

## **How to Order**

Order this fastener from our inventory online by visiting <a href="https://military-fasteners.com/rivets/blind+rivets/MS90354U1006">https://military-fasteners.com/rivets/blind+rivets/MS90354U1006</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.