

**Description**

MS90354 series rivet

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS90354U1009
Minimum Qty (MOQ):	5
NSN:	5320-01-274-7294
Schedule B:	7318.15.2010
ECCN:	9A991
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed



\* See page 2 for technical characteristics

# P/N MS90354U1009 Specifications

Fastener Length:	0.819 Inches Maximum
Head Style:	Straight Pan
Head Height:	0.131 Inches Minimum And 0.141 Inches Maximum
Shank Diameter:	0.310 Inches Minimum And 0.312 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.480 Inches Minimum And 0.522 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.531 Nominal Mils And 0.595 Nominal Centimeters
Minimum Tensile Strength:	112000 Pounds Per Square Inch
Hardness Rating:	326.0 Knoop Minimum Sleeve And 466.0 Knoop Maximum Sleeve
Hardness Rating:	48.0 Rockwell C Minimum Stem And 53.0 Rockwell C Maximum Stem
Special Features:	Single Action Fastener Installed With A Single Action Tool
Material:	Steel Sleeve
Material:	Steel Stem
Material Document And Classification:	Astm-a-331 Assn Std Single Material Response Sleeve
Material Document And Classification:	Astm-a-331 Assn Std Single Material Response Stem
Surface Treatment:	Cadmium Sleeve And Chromate Sleeve
Surface Treatment:	Cadmium Stem
Surface Treatment Document And Classification:	Qq-p-416,ty 1,cl 3 Fed Spec Single Treatment Response Stem
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Sleeve

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS90354U1009> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.