

**Description**

Rivet part number

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS90354U1212D
Minimum Qty (MOQ):	1 EA
NSN:	5320-01-412-3551
Schedule B:	7318.23.0000
ECCN:	9A991
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N MS90354U1212D Specifications

<b>Fastener Length:</b>	1.048 Inches Nominal
<b>Head Style:</b>	Straight Pan
<b>Head Height:</b>	0.195 Inches Minimum And 0.205 Inches Maximum
<b>Shank Diameter:</b>	0.372 Inches Minimum And 0.374 Inches Maximum
<b>Head Major Diameter:</b>	0.580 Inches Minimum And 0.627 Inches Maximum
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Lubrication:</b>	Dry Film
<b>Grip Length:</b>	0.719 Inches Minimum And 0.782 Inches Maximum
<b>Minimum Tensile Strength:</b>	7500 Pounds Per Square Inch
<b>Shear Strength:</b>	12200 Single Pounds Per Square Inch
<b>Material:</b>	Steel Comp 8740 Overall
<b>Material Document And Classification:</b>	Astm 331 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Aluminum Overall

## How to Order

Order this rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS90354U1212D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.