

Description

Rivet part number

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS90354U1212D
Minimum Qty (MOQ):	1 EA
NSN:	5320-01-412-3551
Schedule B:	7318.23.0000
ECCN:	9A991
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS90354U1212D Specifications

Fastener Length:	1.048 Inches Nominal
Head Style:	Straight Pan
Head Height:	0.195 Inches Minimum And 0.205 Inches Maximum
Shank Diameter:	0.372 Inches Minimum And 0.374 Inches Maximum
Head Major Diameter:	0.580 Inches Minimum And 0.627 Inches Maximum
Expansion Device:	Serrated Stem-type W
Lubrication:	Dry Film
Grip Length:	0.719 Inches Minimum And 0.782 Inches Maximum
Minimum Tensile Strength:	7500 Pounds Per Square Inch
Shear Strength:	12200 Single Pounds Per Square Inch
Material:	Steel Comp 8740 Overall
Material Document And Classification:	Astm 331 Assn Std Single Material Response Overall
Surface Treatment:	Aluminum Overall

How to Order

Order this rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS90354U1212D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.