

## P/N MS9061-06

### **Description**

Fastener Length: 1/2", Hole Diameter: 5/64", Thread: 1/4-28, Thread Length: 3/8"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model:	MS906106
Minimum Qty (MOQ):	1 EA
NSN:	5306-00-813-9620
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N MS9061-06 Specifications

Thread Class:	1a
Thread Direction:	Right-hand
Thread Length:	0.367 Inches Minimum
Fastener Length:	0.500 Inches Nominal
Head Style:	Double Hexagon W/hole
Head Height:	0.330 Inches Nominal
Width Between Flats:	0.304 Inches Minimum And 0.313 Inches Maximum
Extended Washer Diameter:	0.438 Inches Nominal
Extended Washer Thickness:	0.060 Inches Minimum And 0.070 Inches Maximum
Hole Diameter:	0.070 Inches Nominal
Nominal Thread Diameter:	0.250 Inches
Hole Quantity:	4
Hole Type:	Drilled
Features Provided:	Finished Head
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	130000 Pounds Per Square Inch
Hardness Rating:	248.0 Brinell Standard Minimum Overall And 341.0 Brinell Standard Maximum Overall
Minimum Yield Strength:	85000 Pounds Per Square Inch
Hole Configuration Style:	Double Hexagon Longitudinal Hole
Surface Finish:	32.0 Microinches Threads
Surface Finish:	63.0 Microinches Bearing Surface Of Head
Surface Finish:	63.0 Microinches Grip
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5732 Assn Std Single Material Response Overall
Thread Series Designator:	Unf

## **How to Order**

Order this bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/machine+bolts/MS9061-06">https://military-fasteners.com/bolts/machine+bolts/MS9061-06</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.