

**Description**

Fastener Length: 0-3/4", Hole Diameter: 5/64", Thread: 1/4-28, Thread Length: 3/4"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                    |                  |
|--------------------|------------------|
| SKU / Model:       | MS906126         |
| Minimum Qty (MOQ): | 5 EA             |
| NSN:               | 5306-00-071-1415 |
| Schedule B:        | 7318.15.8085     |
| ECCN:              | EAR99            |

NO IMAGE  
AVAILABLE

## P/N MS9061-26 Specifications

|  |   |
|--|---|
| <b>Thread Class:</b>                         | 1a  |
| <b>Thread Direction:</b>                     | Right-hand  |
| <b>Thread Length:</b>                        | 0.740 Inches Minimum And 0.820 Inches Maximum                       |
| <b>Fastener Length:</b>                      | 0.740 Inches Minimum And 1.760 Inches Maximum                       |
| <b>Head Style:</b>                           | Double Hexagon W/hole   |
| <b>Head Height:</b>                          | 0.320 Inches Minimum And 0.340 Inches Maximum                       |
| <b>Width Between Flats:</b>                  | 0.304 Inches Minimum And 0.313 Inches Maximum                       |
| <b>Extended Washer Diameter:</b>             | 0.438 Inches Nominal  |
| <b>Extended Washer Thickness:</b>            | 0.060 Inches Minimum And 0.070 Inches Maximum                       |
| <b>Hole Diameter:</b>                        | 0.070 Inches Nominal  |
| <b>Nominal Thread Diameter:</b>              | 0.250 Inches  |
| <b>Grip Length:</b>                          | 0.940 Inches Minimum And 1.000 Inches Maximum                       |
| <b>Hole Quantity:</b>                        | 4   |
| <b>Hole Type:</b>                            | Drilled   |
| <b>Features Provided:</b>                    | Finished Head   |
| <b>Thread Quantity Per Inch:</b>             | 28  |
| <b>Minimum Tensile Strength:</b>             | 130000 Pounds Per Square Inch                                       |
| <b>Hardness Rating:</b>                      | 24.0 Rockwell C Minimum Overall And 35.0 Rockwell C Maximum Overall |
| <b>Minimum Yield Strength:</b>               | 85000 Pounds Per Square Inch  |
| <b>Hole Configuration Style:</b>             | Double Hexagon Longitudinal Hole                                    |
| <b>Surface Finish:</b>                       | 63.0 Microinches Bearing Surface Of Head                            |
| <b>Surface Finish:</b>                       | 63.0 Microinches Grip   |
| <b>Material:</b>                             | Iron Alloy 660 Overall  |
| <b>Material Document And Classification:</b> | Ams 5732 Assn Std Single Material Response Overall                  |
| <b>Thread Series Designator:</b>             | Unf   |

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS9061-26> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.