



Military-Fasteners.com

P/N MS9062-11

Description

Fastener Length: 15/16", Hole Diameter: 5/64", Thread: 5/16-24, Thread Length: 55/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS906211
Minimum Qty (MOQ):	5 EA
NSN:	5306-00-081-5890
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS9062-11 Specifications

Thread Class:	1a
Thread Direction:	Right-hand
Thread Length:	0.845 Inches Minimum And 0.948 Inches Maximum
Fastener Length:	0.928 Inches Minimum And 0.948 Inches Maximum
Head Style:	Double Hexagon W/hole
Head Height:	0.375 Inches Nominal
Width Between Flats:	0.367 Inches Minimum And 0.376 Inches Maximum
Extended Washer Diameter:	0.500 Inches Nominal
Extended Washer Thickness:	0.070 Inches Minimum And 0.080 Inches Maximum
Hole Diameter:	0.070 Inches Nominal
Nominal Thread Diameter:	0.312 Inches
Hole Quantity:	4
Hole Type:	Drilled
Features Provided:	Finished Head
Thread Quantity Per Inch:	24
Hole Configuration Style:	Double Hexagon Longitudinal Hole
Surface Finish:	32.0 Microinches Threads
Surface Finish:	63.0 Microinches Bearing Surface Of Head
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5732 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Thread Series Designator:	Unf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS9062-11> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.