



Military-Fasteners.com

P/N MS9062-21

Description

Fastener Length: 1-9/16", Hole Diameter: 7/64", Thread: 5/16-24, Thread Length: 7/8"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS906221
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-173-6779
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

# P/N MS9062-21 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.864 Inches Minimum And 0.924 Inches Maximum
Fastener Length:	1.552 Inches Minimum And 1.572 Inches Maximum
Head Style:	Double Hexagon W/hole
Head Height:	0.365 Inches Minimum And 0.385 Inches Maximum
Width Between Flats:	0.367 Inches Minimum And 0.376 Inches Maximum
Extended Washer Diameter:	0.490 Inches Minimum And 0.510 Inches Maximum
Extended Washer Thickness:	0.070 Inches Minimum And 0.080 Inches Maximum
Hole Diameter:	0.100 Inches Nominal
Nominal Thread Diameter:	0.312 Inches
Grip Length:	0.628 Inches Minimum And 0.688 Inches Maximum
Hole Quantity:	4
Hole Type:	Drilled
Features Provided:	Finished Head
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	130000 Pounds Per Square Inch
Hardness Rating:	24.0 Rockwell C Minimum Overall And 35.0 Rockwell C Maximum Overall
Minimum Yield Strength:	85000 Pounds Per Square Inch
Hole Configuration Style:	Round
Surface Finish:	32.0 Microinches Threads
Surface Finish:	63.0 Microinches Bearing Surface Of Head
Surface Finish:	63.0 Microinches Grip
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5732 Assn Std Single Material Response Overall
Thread Series Designator:	Unf

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS9062-21> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.