

Description

Fastener Length: 31/32", Thread: 1/2-13, Thread Length: 25/32",

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS90725109
Minimum Qty (MOQ):	25
NSN:	5305-00-044-4153
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N MS90725-109 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.769 Inches Minimum
Fastener Length:	0.969 Inches Minimum And 1.000 Inches Maximum
Head Style:	Hexagon
Head Height:	0.302 Inches Minimum And 0.323 Inches Maximum
Width Between Flats:	0.736 Inches Minimum And 0.750 Inches Maximum
Nominal Thread Diameter:	0.500 Inches
Thread Quantity Per Inch:	13
Minimum Tensile Strength:	120 Pounds Per Square Inch
Hardness Rating:	25.0 Rockwell C Minimum Overall And 34.0 Rockwell C Maximum Overall
Minimum Yield Strength:	85 Pounds Per Square Inch
Surface Finish:	63.0 Microinches Threads
Material:	Steel Overall
Material Document And Classification:	Sae Gr 5 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2 Cl 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unc
Nondefinitive Spec/std Data:	2 Type And 10p Style And 5 Grade

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS90725-109> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.