



Military-Fasteners.com

P/N MS90725-116

Description

Fastener Length: 2-1/4", Thread: 1/2-13, Thread Length: 1-1/4

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

[B1821BH050C225N](#) [BH050C225N](#)

SKU / Model:	MS90725116
Minimum Qty (MOQ):	10
NSN:	5305-00-071-2072
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS90725-116 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	1.250 Inches Minimum And 1.440 Inches Maximum
Fastener Length:	2.250 Inches Nominal
Head Style:	Hexagon
Head Height:	0.302 Inches Minimum And 0.323 Inches Maximum
Width Between Flats:	0.736 Inches Minimum And 0.750 Inches Maximum
End Item Identification:	Mrap Auv Rg-33
Nominal Thread Diameter:	0.500 Inches
Thread Quantity Per Inch:	13
Minimum Tensile Strength:	150000 Pounds Per Square Inch
Hardness Rating:	33.0 Rockwell C Minimum And 39.0 Rockwell C Maximum Overall
Minimum Yield Strength:	120000 Pounds Per Square Inch
Material:	Steel Overall
Material Document And Classification:	Saej429 Grade 8 Assn Std Single Material Response Or Astm A354 Grade Bd Assn Std Single Material Response Overall
Surface Treatment:	Zinc And Chromate Overall
Surface Treatment Document And Classification:	Astm B633 Ty 2 Sc 3 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unc

How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS90725-116> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.