

Description

Length: 1-11/16", Thread: 1/4-20, Thread Length: 3/4", MS90725 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS9072513
Minimum Qty (MOQ):	100
NSN:	5306-01-303-2815
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS90725-13 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.750 Inches Minimum And 0.938 Inches Maximum
Fastener Length:	1.688 Inches Minimum And 1.750 Inches Maximum
Head Style:	Hexagon
Head Height:	0.150 Inches Minimum And 0.163 Inches Maximum
Width Between Flats:	0.428 Inches Minimum And 0.438 Inches Maximum
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.750 Inches Minimum And 1.000 Inches Maximum
Features Provided:	Finished Head
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	120000 Pounds Per Square Inch
Hardness Rating:	25.0 Rockwell C Minimum Overall And 34.0 Rockwell C Maximum Overall
Surface Finish:	63.0 Microinches Threads
Material:	Steel Overall
Material Document And Classification:	Sae Gr 5 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2,cl 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unc
Nondefinitive Spec/std Data:	1 Type And 10p Style And 5 Grade

How to Order

Order this hexagon head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/hexagon+head+cap+screws/MS90725-13> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.