

P/N MS90725-14

Description

Military-Fasteners.com

Fastener Length: 2-1/64", Thread: 1/4-20, Thread Length: 3/4", MS90725 series screw

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	MS9072514
Minimum Qty (MOQ):	100
NSN:	5305-00-071-2237
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N MS90725-14 Specifications

Thread Direction:Right-handThread Length:0.750 Inches Minimum And 0.938 Inches MaximumFastener Length:2.000 Inches NominalHead Style:HexagonHead Height:0.150 Inches Minimum And 0.163 Inches MaximumWidth Between Flats:0.428 Inches Minimum And 0.438 Inches MaximumNominal Thread Diameter:0.250 InchesThread Quantity Per Inch:20Minimum Tensile Strength:120000 Pounds Per Square InchHardness Rating:0.300 Pounds Per Square InchMinimum Yield Strength:Stool Pounds Per Square InchMaterial:Stool Pounds Per Square I	Thread Direction:Right-handThread Direction:0.750 Inches Minimum And 0.938 Inches MaximumFastener Length:0.750 Inches MominalFastener Length:0.000 Inches NominalHead Style:HexagonHead Height:0.150 Inches Minimum And 0.163 Inches MaximumWidth Between Flats:0.428 Inches Minimum And 0.438 Inches MaximumNominal Thread Diameter:0.250 InchesThread Quantity Per Inch:0.250 InchesMinimum Tensile Strength:120000 Pounds Per Square InchHardness Rating:0.300 Pounds Per Square InchMinimum Yield Strength:Stoel OverallMaterial:Stoel OverallMaterial:Steel OverallSurface Treatment:Sae Gr 5 Assn Std Single Material Response OverallSurface Treatment Document And Classification:Sae -ams-qq-p-416 Assn Std Single Treatment Response Overall		_
Thread Length:0.750 Inches Minimum And 0.938 Inches MaximumFastener Length:2.000 Inches NominalHead Style:HexagonHead Height:0.150 Inches Minimum And 0.163 Inches MaximumWidth Between Flats:0.428 Inches Minimum And 0.438 Inches MaximumNominal Thread Diameter:0.250 InchesThread Quantity Per Inch:20Minimum Tensile Strength:120000 Pounds Per Square InchMinimum Yield Strength:300 Pounds Per Square InchMaterial:Steel OverallMaterial Document And Classification:Sac Gr 5 Assn Std Single Material Response OverallSurface Treatment:Cadmium Overall And Chromate Overall	Thread Length:0.750 Inches Minimum And 0.938 Inches MaximumFastener Length:2.000 Inches NominalHead Style:HexagonHead Height:0.150 Inches Minimum And 0.163 Inches MaximumWidth Between Flats:0.428 Inches Minimum And 0.438 Inches MaximumNominal Thread Diameter:0.250 InchesThread Quantity Per Inch:20Minimum Tensile Strength:120000 Pounds Per Square InchMinimum Tensile Strength:20.000 Pounds Per Square InchMinimum Yield Strength:85000 Pounds Per Square InchMaterial:Steel OverallMaterial:Steel OverallMaterial:Steel OverallSurface Treatment:Cadmium Overall And Chromate OverallBurface Treatment:Sae ars-sq-qp-416 Assn Std Single Treatment Response Overall	Thread Class:	2a
Fastener Length:2.000 Inches NominalHead Style:HexagonHead Height:0.150 Inches Minimum And 0.163 Inches MaximumWidth Between Flats:0.428 Inches Minimum And 0.438 Inches MaximumNominal Thread Diameter:0.250 InchesThread Quantity Per Inch:20Minimum Tensile Strength:120000 Pounds Per Square InchHardness Rating:23.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum OverallMaterial:Steel OverallMaterial Document And Classification:Sae Gr 5 Assn Std Single Material Response OverallSurface Treatment:Cadmium Overall And Chromate Overall	Fastener Length:2.000 Inches NominalHead Style:HexagonHead Height:0.150 Inches Minimum And 0.163 Inches MaximumWidth Between Flats:0.428 Inches Minimum And 0.438 Inches MaximumNominal Thread Diameter:0.428 Inches Minimum And 0.438 Inches MaximumThread Quantity Per Inch:0.250 InchesMinimum Tensile Strength:12000 Pounds Per Square InchHardness Rating:0.300 Pounds Per Square InchMinimum Yield Strength:Steel OverallMaterial:Steel OverallMaterial Document And Classification:Sae Gr 5 Assn Std Single Material Response OverallSurface Treatment:Gadmium Overall And Classification:	Thread Direction:	Right-hand
Head Style:HexagonHead Height:0.150 Inches Minimum And 0.163 Inches MaximumWidth Between Flats:0.428 Inches Minimum And 0.438 Inches MaximumNominal Thread Diameter:0.250 InchesThread Quantity Per Inch:20Minimum Tensile Strength:120000 Pounds Per Square InchHardness Rating:3.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum OverallMinimum Yield Strength:5000 Pounds Per Square InchMaterial:Steel OverallMaterial Document And Classification:Sae Gr 5 Assn Std Single Material Response OverallSurface Treatment:Cadmium Overall And Chromate Overall	Head Style:HexagonHead Height:0.150 Inches Minimum And 0.163 Inches MaximumWidth Between Flats:0.428 Inches Minimum And 0.438 Inches MaximumNominal Thread Diameter:0.250 InchesThread Quantity Per Inch:20Minimum Tensile Strength:120000 Pounds Per Square InchHardness Rating:23.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum OverallMinimum Yield Strength:85000 Pounds Per Square InchMaterial:Steel OverallMaterial Document And Classification:Sae Gr 5 Assn Std Single Material Response OverallSurface Treatment:Gadmium Overall And Chromate Overall	Thread Length:	0.750 Inches Minimum And 0.938 Inches Maximum
Head Height:0.150 Inches Minimum And 0.163 Inches MaximumWidth Between Flats:0.428 Inches Minimum And 0.438 Inches MaximumNominal Thread Diameter:0.250 InchesThread Quantity Per Inch:20Minimum Tensile Strength:120000 Pounds Per Square InchHardness Rating:23.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum OverallMinimum Yield Strength:Steel OverallMaterial:Steel OverallMaterial Document And Classification:Sae Gr 5 Assn Std Single Material Response OverallSurface Treatment:Cadmium Overall And Chromate Overall	Head Height:0.150 Inches Minimum And 0.163 Inches MaximumWidth Between Flats:0.428 Inches Minimum And 0.438 Inches MaximumNominal Thread Diameter:0.250 InchesThread Quantity Per Inch:20Minimum Tensile Strength:120000 Pounds Per Square InchHardness Rating:23.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum OverallMinimum Yield Strength:85000 Pounds Per Square InchMaterial:Steel OverallMaterial Document And Classification:Sae Gr 5 Assn Std Single Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Sae-ams-qq-p-416 Assn Std Single Treatment Response Overall	Fastener Length:	2.000 Inches Nominal
Width Between Flats:0.428 Inches Minimum And 0.438 Inches MaximumNominal Thread Diameter:0.250 InchesThread Quantity Per Inch:20Minimum Tensile Strength:120000 Pounds Per Square InchHardness Rating:23.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum OverallMinimum Yield Strength:85000 Pounds Per Square InchMaterial:Steel OverallMaterial:Steel OverallMaterial Document And Classification:Sae Gr 5 Assn Std Single Material Response OverallSurface Treatment:Cadmium Overall And Chromate Overall	Width Between Flats:0.428 Inches Minimum And 0.438 Inches MaximumNominal Thread Diameter:0.250 InchesThread Quantity Per Inch:20Minimum Tensile Strength:120000 Pounds Per Square InchHardness Rating:23.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum OverallMinimum Yield Strength:85000 Pounds Per Square InchMaterial:Steel OverallMaterial Document And Classification:Sa G r 5 Assn Std Single Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Response OverallSae-ams-qq-p-416 Assn Std Single Treatment Response Overall	Head Style:	Hexagon
Nominal Thread Diameter:0.250 InchesThread Quantity Per Inch:20Minimum Tensile Strength:120000 Pounds Per Square InchHardness Rating:23.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum OverallMinimum Yield Strength:85000 Pounds Per Square InchMaterial:Steel OverallMaterial Document And Classification:Sae Gr 5 Assn Std Single Material Response OverallSurface Treatment:Cadmium Overall And Chromate Overall	Nominal Thread Diameter:0.250 InchesThread Quantity Per Inch:20Minimum Tensile Strength:120000 Pounds Per Square InchHardness Rating:23.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum OverallMinimum Yield Strength:85000 Pounds Per Square InchMaterial:Steel OverallMaterial Document And Classification:Sae Gr 5 Assn Std Single Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Sae-ams-qq-p-416 Assn Std Single Treatment Response Overall	Head Height:	0.150 Inches Minimum And 0.163 Inches Maximum
Thread Quantity Per Inch:20Minimum Tensile Strength:120000 Pounds Per Square InchHardness Rating:23.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum OverallMinimum Yield Strength:85000 Pounds Per Square InchMaterial:Steel OverallMaterial Document And Classification:Sae Gr 5 Assn Std Single Material Response OverallSurface Treatment:Cadmium Overall And Chromate Overall	Thread Quantity Per Inch:20Minimum Tensile Strength:120000 Pounds Per Square InchHardness Rating:23.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum OverallMinimum Yield Strength:85000 Pounds Per Square InchMaterial:Steel OverallMaterial Document And Classification:Sae Gr 5 Assn Std Single Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment And Classification:Sae-ams-qq-p-416 Assn Std Single Treatment Response Overall	Width Between Flats:	0.428 Inches Minimum And 0.438 Inches Maximum
Minimum Tensile Strength:120000 Pounds Per Square InchHardness Rating:23.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum OverallMinimum Yield Strength:85000 Pounds Per Square InchMaterial:Steel OverallMaterial Document And Classification:Sae Gr 5 Assn Std Single Material Response OverallSurface Treatment:Cadmium Overall And Chromate Overall	Minimum Tensile Strength:120000 Pounds Per Square InchHardness Rating:23.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum OverallMinimum Yield Strength:85000 Pounds Per Square InchMaterial:Steel OverallMaterial Document And Classification:Sae Gr 5 Assn Std Single Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallBurface Treatment:Sae-ams-qr-p-416 Assn Std Single Treatment Response Overall	Nominal Thread Diameter:	0.250 Inches
Hardness Rating:23.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum OverallMinimum Yield Strength:85000 Pounds Per Square InchMaterial:Steel OverallMaterial Document And Classification:Sae Gr 5 Assn Std Single Material Response OverallSurface Treatment:Cadmium Overall And Chromate Overall	Hardness Rating:23.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum OverallMinimum Yield Strength:85000 Pounds Per Square InchMaterial:Steel OverallMaterial Document And Classification:Sae Gr 5 Assn Std Single Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Sae-ams-qq-p-416 Assn Std Single Treatment Response Overall	Thread Quantity Per Inch:	20
Minimum Yield Strength:85000 Pounds Per Square InchMaterial:Steel OverallMaterial Document And Classification:Sae Gr 5 Assn Std Single Material Response OverallSurface Treatment:Cadmium Overall And Chromate Overall	Minimum Yield Strength:85000 Pounds Per Square InchMaterial:Steel OverallMaterial Document And Classification:Sae Gr 5 Assn Std Single Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Sae-ams-qq-p-416 Assn Std Single Treatment Response Overall	Minimum Tensile Strength:	120000 Pounds Per Square Inch
Material: Steel Overall Material Document And Classification: Sae Gr 5 Assn Std Single Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall	Material:Steel OverallMaterial Document And Classification:Sae Gr 5 Assn Std Single Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Sae-ams-qq-p-416 Assn Std Single Treatment Response Overall	Hardness Rating:	23.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Material Document And Classification: Sae Gr 5 Assn Std Single Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall	Material Document And Classification:Sae Gr 5 Assn Std Single Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Sae-ams-qq-p-416 Assn Std Single Treatment Response Overall	Minimum Yield Strength:	85000 Pounds Per Square Inch
Surface Treatment: Cadmium Overall And Chromate Overall	Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Sae-ams-qq-p-416 Assn Std Single Treatment Response Overall	Material:	Steel Overall
	Surface Treatment Document And Classification: Sae-ams-qq-p-416 Assn Std Single Treatment Response Overall	Material Document And Classification:	Sae Gr 5 Assn Std Single Material Response Overall
Surface Treatment Document And Classification: Sae-ams-gg-p-416 Assn Std Single Treatment Response Overall		Surface Treatment:	Cadmium Overall And Chromate Overall
	Thread Series Designator: Unc	Surface Treatment Document And Classification:	Sae-ams-qq-p-416 Assn Std Single Treatment Response Overall
Thread Series Designator: Unc		Thread Series Designator:	Unc

How to Order

Order this hexagon head cap screw from our inventory online by visiting <u>https://military-fasteners.com/screws/hexagon+head+cap+screws/MS90725-14</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out<u>here</u> to complete your order.