

P/N MS90725-18

Description

Fastener Length: 2-29/32", Thread: 1/4-20, Thread Length: 3/4",

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: MS9072518

Minimum Qty (MOQ): 50

NSN: 5305-00-071-2233

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









P/N MS90725-18 Specifications

| Thread Class: | 2a |
|--|---|
| Thread Direction: | Right-hand |
| Thread Length: | 0.740 Inches Minimum And 0.750 Inches Maximum |
| Fastener Length: | 2.906 Inches Minimum And 3.000 Inches Maximum |
| Head Style: | Hexagon |
| Head Height: | 0.150 Inches Minimum And 0.163 Inches Maximum |
| Width Between Flats: | 0.428 Inches Minimum And 0.437 Inches Maximum |
| Nominal Thread Diameter: | 0.250 Inches |
| Thread Quantity Per Inch: | 20 |
| Minimum Tensile Strength: | 120000 Pounds Per Square Inch |
| Hardness Rating: | 25.0 Rockwell C Minimum Overall And 34.0 Rockwell C Maximum Overall |
| Material: | Steel Overall |
| Material Document And Classification: | Sae Gr 5 Assn Std Single Material Response Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Sae/ams Qq-p-416 Ty2cl3 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unc |

How to Order

Order this machine screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/MS90725-18 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.