

**Description**

Fastener Length: 27/64", Thread: 5/16-18, Thread Length: 7/16"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                    |                  |
|--------------------|------------------|
| SKU / Model:       | MS9072528        |
| Minimum Qty (MOQ): | 20 EA            |
| NSN:               | 5306-00-225-8493 |
| Schedule B:        | 7318.15.6080     |
| ECCN:              | EAR99            |

NO IMAGE  
AVAILABLE

## P/N MS90725-28 Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>                                  | 2a  |
| <b>Thread Direction:</b>                              | Right-hand  |
| <b>Thread Length:</b>                                 | 0.438 Inches Maximum  |
| <b>Fastener Length:</b>                               | 0.407 Inches Minimum And 0.438 Inches Maximum                       |
| <b>Head Style:</b>                                    | Hexagon   |
| <b>Head Height:</b>                                   | 0.195 Inches Minimum And 0.211 Inches Maximum                       |
| <b>Width Between Flats:</b>                           | 0.489 Inches Minimum And 0.500 Inches Maximum                       |
| <b>Nominal Thread Diameter:</b>                       | 0.312 Inches  |
| <b>Features Provided:</b>                             | Finished Head   |
| <b>Thread Quantity Per Inch:</b>                      | 18  |
| <b>Minimum Tensile Strength:</b>                      | 120000 Pounds Per Square Inch                                       |
| <b>Hardness Rating:</b>                               | 25.0 Rockwell C Minimum Overall And 34.0 Rockwell C Maximum Overall |
| <b>Surface Finish:</b>                                | 63.0 Microinches Threads  |
| <b>Material:</b>                                      | Steel Overall   |
| <b>Material Document And Classification:</b>          | Sae Gr 5 Assn Std Single Material Response Overall                  |
| <b>Surface Treatment:</b>                             | Cadmium Overall And Chromate Overall                                |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-416,ty 2 Cl 2 Fed Spec Single Treatment Response Overall       |
| <b>Thread Series Designator:</b>                      | Unc   |
| <b>Nondefinitive Spec/std Data:</b>                   | 2 Type And 10p Style And 5 Grade                                    |

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS90725-28> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.