

**Description**

Fastener Length: 23/32", Thread: 5/16-18, Thread Length: 19/32", MS90725 series screw

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS9072532
Minimum Qty (MOQ):	50
NSN:	5306-00-226-4825
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

## P/N MS90725-32 Specifications

<b>Thread Class:</b>	2a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.580 Inches Minimum And 0.750 Inches Maximum
<b>Fastener Length:</b>	0.719 Inches Minimum And 0.750 Inches Maximum
<b>Head Style:</b>	Hexagon
<b>Head Height:</b>	0.195 Inches Minimum And 0.211 Inches Maximum
<b>Width Between Flats:</b>	0.489 Inches Minimum And 0.500 Inches Maximum
<b>End Item Identification:</b>	Rg-33 Auv Mrap
<b>Nominal Thread Diameter:</b>	0.312 Inches
<b>Features Provided:</b>	Finished Head
<b>Thread Quantity Per Inch:</b>	18
<b>Minimum Tensile Strength:</b>	150000 Pounds Per Square Inch
<b>Criticality Code Justification:</b>	Feat
<b>Surface Finish:</b>	63.0 Microinches Threads
<b>Special Features:</b>	Weapon System Essential
<b>Material:</b>	Steel Overall
<b>Material Document And Classification:</b>	Sae J429,gr 8 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Zinc And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Astm B633 Ty 2 Sc 3 Assn Std Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unc

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS90725-32> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.