



★ FASTENERS

Military-Fasteners.com

P/N MS90725-33

Description

Fastener Length: 7/8", Thread: 5/16-18, Thread Length: 7/8", MS90725 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS9072533 |
| Minimum Qty (MOQ): | 25 |
| NSN: | 5306-00-225-8498 |
| Schedule B: | 7318.15.6080 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N MS90725-33 Specifications

| | |
|---|---|
| Thread Class: | 2a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.875 Inches Maximum |
| Fastener Length: | 0.875 Inches Nominal |
| Head Style: | Hexagon |
| Head Height: | 0.195 Inches Minimum And 0.211 Inches Maximum |
| Width Between Flats: | 0.489 Inches Minimum And 0.500 Inches Maximum |
| Nominal Thread Diameter: | 0.312 Inches |
| Features Provided: | Finished Head |
| Thread Quantity Per Inch: | 18 |
| Minimum Tensile Strength: | 120000 Pounds Per Square Inch |
| Hardness Rating: | 23.0 Rockwell C Minimum And 32.0 Rockwell C Maximum Overall |
| Material: | Steel Overall |
| Material Document And Classification: | Sae Gr 5 Assn Std Single Material Response Overall |
| Surface Treatment: | Cadmium And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2 Cl 2 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unc |
| Nondefinitive Spec/std Data: | 2 Type And 10p Style And 5 Grade |

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS90725-33> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.