

## P/N MS90725-35

## **Description**

Fastener Length: 1-1/16", Thread: 5/16-18, Thread Length: 7/8",

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: MS9072535

Minimum Qty (MOQ): 100

NSN: 5306-00-226-4828

Schedule B: 7318.15.6080

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









# P/N MS90725-35 Specifications

read Class: 2	2a
read Direction:	Right-hand
read Length: 0	0.875 Inches Minimum And 1.063 Inches Maximum
stener Length: 1	1.063 Inches Minimum And 1.125 Inches Maximum
ead Style:	Hexagon
ead Height: 0	0.195 Inches Minimum And 0.211 Inches Maximum
idth Between Flats: 0	0.489 Inches Minimum And 0.500 Inches Maximum
End Item Identification:	Mrap Rg-33; Mrap - Matv With Cs13 Pop
ominal Thread Diameter: 0	0.312 Inches
ip Length: 0	0.250 Inches Nominal
atures Provided:	Finished Head
read Quantity Per Inch:	18
nimum Tensile Strength: 1	150000 Pounds Per Square Inch
rface Finish: 6	63.0 Microinches Threads
aterial: S	Steel Overall
aterial Document And Classification:	Sae J429 Grade 8 Assn Std Single Material Response Overall Or Astm A354 Grade Bd Assn Std Single Material Response Overall
aterial Document And Classification:	Sae J429 Grade 8 Assn Std Single Material Response Or Astm A354 Grade Bd Assn Std Single Material Response Overall
rface Treatment:	Zinc Overall And Chromate Overall
rface Treatment:	Zinc And Chromate Overall
rface Treatment Document And	Astm B633 Ty 2 Sc 3 Assn Std Single Treatment Response Overall
assification:	Astri B055 Ty 2 Sc 5 Assri Std Single Treatment Nesponse Overall

## **How to Order**

Order this machine screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/machine+screws/MS90725-35">https://military-fasteners.com/screws/machine+screws/MS90725-35</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.