

Description

Fastener Length: 3-1/64", Thread: 5/16-18, Thread Length: 7/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS9072544
Minimum Qty (MOQ):	5 EA
NSN:	5306-00-225-8508
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS90725-44 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.874 Inches Minimum
Fastener Length:	3.000 Inches Nominal
Head Style:	Hexagon
Head Height:	0.195 Inches Minimum And 0.211 Inches Maximum
Width Between Flats:	0.489 Inches Minimum And 0.500 Inches Maximum
Nominal Thread Diameter:	0.312 Inches
Features Provided:	Finished Head
Thread Quantity Per Inch:	18
Minimum Tensile Strength:	120000 Pounds Per Square Inch
Hardness Rating:	23.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Material:	Steel Overall
Material Document And Classification:	Sae Gr 5 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses Overall
Thread Series Designator:	Unc
Nondefinitive Spec/std Data:	2 Type And 10- Style And 5 Grade

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS90725-44> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.