

Description

Fastener Length: 4-", Thread: 1/4-18, Thread Length: "

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | MS9072548 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5306-00-225-8512 |
| Schedule B: | 7318.15.8085 |
| ECCN: | 9A991 |

NO IMAGE
AVAILABLE

P/N MS90725-48 Specifications

| | |
|-------------------------------------------------------|---------------------------------------------------------------------|
| Thread Class: | 2a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.874 Inches Minimum |
| Fastener Length: | 4.000 Inches Nominal |
| Head Style: | Hexagon |
| Head Height: | 0.195 Inches Minimum And 0.211 Inches Maximum |
| Width Between Flats: | 0.489 Inches Minimum And 0.500 Inches Maximum |
| Nominal Thread Diameter: | 0.312 Inches |
| Features Provided: | Finished Head |
| Thread Quantity Per Inch: | 18 |
| Minimum Tensile Strength: | 120000 Pounds Per Square Inch |
| Hardness Rating: | 23.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall |
| Material: | Steel Overall |
| Material Document And Classification: | Sae Gr 5 Assn Std Single Material Response Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2 Cl 2 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unc |
| Nondefinitive Spec/std Data: | 2 Type And 10p Style And 5 Grade |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS90725-48> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.