

Description

Fastener Length: 1/2", Thread: 3/8-16, Thread Length: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS9072555
Minimum Qty (MOQ):	20 EA
NSN:	5305-00-269-3206
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N MS90725-55 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.313 Inches Minimum And 0.500 Inches Maximum
Fastener Length:	0.469 Inches Minimum And 0.500 Inches Maximum
Head Style:	Hexagon
Head Height:	0.226 Inches Minimum And 0.243 Inches Maximum
Width Between Flats:	0.551 Inches Minimum And 0.562 Inches Maximum
Nominal Thread Diameter:	0.375 Inches
Thread Quantity Per Inch:	16
Minimum Tensile Strength:	120000 Pounds Per Square Inch
Hardness Rating:	23.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Minimum Yield Strength:	85000 Pounds Per Square Inch
Material:	Steel Overall
Material Document And Classification:	Sae Gr 5 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Sae/ams Qq-p-416 Ty2cl3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unc

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS90725-55> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.