

P/N MS90725-6

Description

Fastener Length: 3/4", Thread: 1/4-20, Thread Length: 5/8", cadmium yellow, MS90725 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: MS907256


Minimum Qty (MOQ): 100

NSN: 5305-00-068-0502

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)















^{*} See page 2 for technical characteristics

P/N MS90725-6 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.625 Inches Minimum
Fastener Length:	0.750 Inches Nominal
Head Style:	Hexagon
Head Height:	0.150 Inches Minimum And 0.163 Inches Maximum
Width Between Flats:	0.428 Inches Minimum And 0.438 Inches Maximum
End Item Identification:	3990-01-444-6174 Bitum Distributor
End Item Identification:	3990-01-444-6174 Bitum Distributor; Mrap - Cougar Tow
Nominal Thread Diameter:	0.250 Inches
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	120000 Pounds Per Square Inch
Hardness Rating:	23.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Hardness Rating:	23.0 Rockwell C Minimum And 32.0 Rockwell C Maximum Overall
Material:	Steel Overall
Material Document And Classification:	Sae Gr 5 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment:	Cadmium And Chromate Overall
Surface Treatment Document And Classification:	Sae/ams Qq-p-416, Ty2cl3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unc

How to Order

Order this hexagon head cap screw from our inventory online by visiting https://military-fasteners.com/screws/hexagon+head+cap+screws/MS90725-6 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.