



Military-Fasteners.com

P/N MS90725-75

Description

Fastener Length: 4-5/32", Thread: 3/8-16, Thread Length: 1-1/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS9072575 |
| Minimum Qty (MOQ): | 1 EA |
| NSN: | 5305-00-269-3225 |
| Schedule B: | 7318.15.6080 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N MS90725-75 Specifications

| | |
|---|---|
| Thread Class: | 2a |
| Thread Direction: | Right-hand |
| Thread Length: | 1.000 Inches Minimum And 1.188 Inches Maximum |
| Fastener Length: | 4.156 Inches Minimum And 4.250 Inches Maximum |
| Head Style: | Hexagon |
| Head Height: | 0.226 Inches Minimum And 0.243 Inches Maximum |
| Width Between Flats: | 0.551 Inches Minimum And 0.562 Inches Maximum |
| Nominal Thread Diameter: | 0.375 Inches |
| Thread Quantity Per Inch: | 16 |
| Minimum Tensile Strength: | 120000 Pounds Per Square Inch |
| Hardness Rating: | 25.0 Rockwell C Minimum Overall And 34.0 Rockwell C Maximum Overall |
| Surface Finish: | 63.0 Microinches Threads |
| Material: | Steel Overall |
| Material Document And Classification: | Sae Gr 5 Assn Std Single Material Response Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2 Cl 2 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unc |
| Nondefinitive Spec/std Data: | 2 Type And 10p Style And 5 Grade |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS90725-75> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.