

Description

Fastener Length: 4-1/2", Thread: 3/8-16, Thread Length: 1-3/16

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | MS9072576 |
| Minimum Qty (MOQ): | 5 |
| NSN: | 5305-00-269-3226 |
| Schedule B: | 7318.15.8085 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N MS90725-76 Specifications

| | |
|---|---|
| Thread Class: | 2a |
| Thread Direction: | Right-hand |
| Thread Length: | 1.000 Inches Minimum And 1.188 Inches Maximum |
| Fastener Length: | 4.500 Inches Nominal |
| Head Style: | Hexagon |
| Head Height: | 0.226 Inches Minimum And 0.243 Inches Maximum |
| Width Between Flats: | 0.551 Inches Minimum And 0.562 Inches Maximum |
| Nominal Thread Diameter: | 0.375 Inches |
| Thread Quantity Per Inch: | 16 |
| Minimum Tensile Strength: | 120000 Pounds Per Square Inch |
| Hardness Rating: | 23.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall |
| Minimum Yield Strength: | 85000 Pounds Per Square Inch |
| Material: | Steel Overall |
| Material Document And Classification: | Sae Gr 5 Assn Std Single Material Response Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2 Cl 2 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unc |
| Nondefinitive Spec/std Data: | 2 Type And 10p Style |

How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS90725-76> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.