

Description

Fastener Length: 63/64", Thread: 7/16-14, Thread Length: 63/64", MS90725 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS9072585 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5305-00-069-5573 |
| Schedule B: | 7318.15.6080 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



P/N MS90725-85 Specifications

| | |
|---|---|
| Thread Class: | 2a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.969 Inches Minimum And 1.000 Inches Maximum |
| Fastener Length: | 0.969 Inches Minimum And 1.000 Inches Maximum |
| Head Style: | Hexagon |
| Head Height: | 0.272 Inches Minimum And 0.291 Inches Maximum |
| Width Between Flats: | 0.612 Inches Minimum And 0.625 Inches Maximum |
| Nominal Thread Diameter: | 0.438 Inches |
| Thread Quantity Per Inch: | 14 |
| Minimum Tensile Strength: | 120000 Pounds Per Square Inch |
| Hardness Rating: | 25.0 Rockwell C Minimum Overall And 34.0 Rockwell C Maximum Overall |
| Minimum Yield Strength: | 92000 Pounds Per Square Inch |
| Material: | Steel Overall |
| Material Document And Classification: | Sae J429,grade 5 Assn Std Single Material Response Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unc |
| Specification/standard Data: | 96906-ms90725-85 Government Standard |

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS90725-85> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.