

Description

Fastener Length: 1-1/2", Thread: 7/16-14, Thread Length: 1-1/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS9072589
Minimum Qty (MOQ):	10 EA
NSN:	5305-00-050-1076
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N MS90725-89 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	1.312 Inches Minimum
Fastener Length:	1.438 Inches Minimum And 1.500 Inches Maximum
Head Style:	Hexagon
Head Height:	0.272 Inches Minimum And 0.291 Inches Maximum
Width Between Flats:	0.612 Inches Minimum And 0.625 Inches Maximum
End Item Identification:	Mrap Buffalo Mk2a2
Nominal Thread Diameter:	0.438 Inches
Thread Quantity Per Inch:	14
Minimum Tensile Strength:	120000 Pounds Per Square Inch
Hardness Rating:	25.0 Rockwell C Minimum And 34.0 Rockwell C Maximum Overall
Surface Finish:	63.0 Microinches Threads
Material:	Steel Overall
Material Document And Classification:	Sae Gr 5 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2 Cl 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unc
Nondefinitive Spec/std Data:	2 Type And 10p Style And 5 Grade

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS90725-89> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.