

## P/N MS90725-98

## **Description**

Fastener Length: 3-3/4", Thread: 7/16-14, Thread Length: 1-5/16"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: MS9072598

Minimum Qty (MOQ): 25 EA

NSN: 5305-00-069-5582

Schedule B: 7318.15.8085

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N MS90725-98 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	1.125 Inches Minimum And 1.312 Inches Maximum
Fastener Length:	3.750 Inches Nominal
Head Style:	Hexagon
Head Height:	0.272 Inches Minimum And 0.291 Inches Maximum
Width Between Flats:	0.612 Inches Minimum And 0.625 Inches Maximum
Nominal Thread Diameter:	0.438 Inches
Thread Quantity Per Inch:	14
Minimum Tensile Strength:	120000 Pounds Per Square Inch
Hardness Rating:	23.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Minimum Yield Strength:	85000 Pounds Per Square Inch
Material:	Steel Overall
Material Document And Classification:	Sae Gr 5 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unc

## **How to Order**

Order this bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/machine+bolts/MS90725-98">https://military-fasteners.com/bolts/machine+bolts/MS90725-98</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.