

## P/N MS90726-107

## **Description**

Fastener Length: 3/4", Thread: 1/2-20, Thread Length: 3/4

\* Manufacturer certifications are shipped with your order FREE of charge

### Order this part online

#### **Additional Information**


SKU / Model: MS90726107

Minimum Qty (MOQ): 20

NSN: 5305-00-716-8192

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)















<sup>\*</sup> See page 2 for technical characteristics

# P/N MS90726-107 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.597 Inches Minimum And 0.750 Inches Maximum
Fastener Length:	0.719 Inches Minimum And 0.750 Inches Maximum
Head Style:	Hexagon
Head Height:	0.302 Inches Minimum And 0.323 Inches Maximum
Width Between Flats:	0.736 Inches Minimum And 0.750 Inches Maximum
Nominal Thread Diameter:	0.500 Inches
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	120000 Pounds Per Square Inch
Hardness Rating:	25.0 Rockwell C Minimum Overall And 34.0 Rockwell C Maximum Overall
Material:	Steel Comp 1013 Overall Or Steel Comp 1015 Overall Or Steel Comp 1016 Overall Or Steel Comp 1017 Overall Or Steel Comp 1018 Overall Or Steel Comp 1019 Overall Or Steel Comp 1020 Overall Or Steel Comp 1021 Overall Or Steel Comp 1022 Overall Or Steel Comp 1023 Overall Or Steel Comp 1524 Overall Or Steel Comp 1025 Overall Or Steel Comp 1026 Overall Or Steel Comp 1527 Overall Or Steel Comp 1029 Overall Or Steel Comp 1030 Overall Or Steel Comp 1034 Overall Or Steel Comp 1035 Overall Or Steel Comp 1536 Overall Or Steel Comp 1037 Overall Or Steel Comp 1038 Overall Or Steel Comp 1039 Overall Or Steel Comp 1040 Overall Or Steel Comp 1541 Overall
Material Document And Classification:	Sae J429 Gr 5 Assn Std All Material Responses Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2 Cl 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unf
Nondefinitive Spec/std Data:	2 Type And 10p Style

## **How to Order**

