

# P/N MS90726-12

## **Description**

Fastener Length: 1-1/2", Thread: 1/4-28, Thread Length: 15/16", MS90726 series Screw

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

### **Additional Information**

#### **Alternate Part Numbers**

#### B1821BH025F150N

SKU / Model: MS9072612

Minimum Qty (MOQ): 10

NSN: 5305-00-267-8956

Schedule B: 7318.15.2095

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









# P/N MS90726-12 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.750 Inches Minimum And 0.938 Inches Maximum
Fastener Length:	1.500 Inches Nominal
Head Style:	Hexagon
Head Height:	0.150 Inches Minimum And 0.163 Inches Maximum
Width Between Flats:	0.428 Inches Minimum And 0.438 Inches Maximum
Nominal Thread Diameter:	0.250 Inches
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	150000 Pounds Per Square Inch
Hardness Rating:	32.0 Rockwell C Minimum Overall And 38.0 Rockwell C Maximum Overall
Material:	Steel Overall
Material Document And Classification:	Sae J429 Gr 8 Assn Std Single Material Response Overall
Surface Treatment:	Zinc Overall And Chromate Overall
Surface Treatment Document And Classification:	Astm B633 Ty 2 Sc 3 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unf
Nondefinitive Spec/std Data:	2 Type And 10p Style And 8 Grade

## **How to Order**

Order this hexagon head cap screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/hexagon+head+cap+screws/MS90726-12">https://military-fasteners.com/screws/hexagon+head+cap+screws/MS90726-12</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.