

Description

Fastener Length: 5-1/2", Thread: 1/2-20, Thread Length: 1-7/16

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS90726128
Minimum Qty (MOQ):	1
NSN:	5305-00-716-8156
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N MS90726-128 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	1.250 Inches Minimum And 1.438 Inches Maximum
Fastener Length:	5.406 Inches Minimum And 5.500 Inches Maximum
Head Style:	Hexagon
Head Height:	0.302 Inches Minimum And 0.323 Inches Maximum
Width Between Flats:	0.736 Inches Minimum And 0.750 Inches Maximum
Nominal Thread Diameter:	0.500 Inches
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	120000 Pounds Per Square Inch
Hardness Rating:	23.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Minimum Yield Strength:	85000 Pounds Per Square Inch
Material:	Steel Overall
Material Document And Classification:	Sae Gr 5 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses Overall
Thread Series Designator:	Unf

How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS90726-128> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.