

P/N MS90726-134

Description

Fastener Length: 0-63/64", Thread: 1/2-18, Thread Length: 63/64", MS90726 series bolt

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: MS90726134


Minimum Qty (MOQ): 10

NSN: 5305-00-902-9338

Schedule B: 7318.15.8085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)













P/N MS90726-134 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.860 Inches Minimum And 1.000 Inches Maximum
Fastener Length:	0.969 Inches Minimum And 1.000 Inches Maximum
Head Style:	Hexagon
Head Height:	0.348 Inches Minimum And 0.371 Inches Maximum
Width Between Flats:	0.798 Inches Minimum And 0.812 Inches Maximum
Nominal Thread Diameter:	0.562 Inches
Thread Quantity Per Inch:	18
Minimum Tensile Strength:	120000 Pounds Per Square Inch
Hardness Rating:	25.0 Rockwell C Minimum Overall And 34.0 Rockwell C Maximum Overall
Material:	Steel Comp 1013 Overall Or Steel Comp 1015 Overall Or Steel Comp 1016 Overall Or Steel Comp 1017 Overall Or Steel Comp 1018 Overall Or Steel Comp 1019 Overall Or Steel Comp 1020 Overall Or Steel Comp 1021 Overall Or Steel Comp 1022 Overall Or Steel Comp 1023 Overall Or Steel Comp 1524 Overall Or Steel Comp 1025 Overall Or Steel Comp 1026 Overall Or Steel Comp 1527 Overall Or Steel Comp 1039 Overall Or Steel Comp 1034 Overall Or Steel Comp 1035 Overall Or Steel Comp 1536 Overall Or Steel Comp 1037 Overall Or Steel Comp 1038 Overall Or Steel Comp 1039 Overall Or Steel Comp 1040 Overall Or Steel Comp 1541 Overall
Material Document And Classification:	66 Fed Std All Material Responses Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unf
Nondefinitive Spec/std Data:	2 Type And 10p Style

How to Order

