

**Description**

Fastener Length: 2", Thread: 5/8-18, Thread Length: 1-11/16", REPLACED BY B1821BH063F200N

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS90726164
Minimum Qty (MOQ):	5
NSN:	5305-00-725-4105
ECCN:	EAR99



\* See page 2 for technical characteristics

## P/N MS90726-164 Specifications

<b>Thread Class:</b>	2a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	1.500 Inches Minimum And 1.688 Inches Maximum
<b>Fastener Length:</b>	2.000 Inches Nominal
<b>Head Style:</b>	Hexagon
<b>Head Height:</b>	0.378 Inches Minimum And 0.403 Inches Maximum
<b>Width Between Flats:</b>	0.922 Inches Minimum And 0.938 Inches Maximum
<b>Nominal Thread Diameter:</b>	0.625 Inches
<b>Thread Quantity Per Inch:</b>	18
<b>Minimum Tensile Strength:</b>	120000 Pounds Per Square Inch
<b>Hardness Rating:</b>	23.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
<b>Minimum Yield Strength:</b>	85000 Pounds Per Square Inch
<b>Material:</b>	Steel Overall
<b>Material Document And Classification:</b>	Sae Gr 5 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unf

## How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS90726-164> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.