

Description

Fastener Length: 3-1/2", Thread: 5/8-18, Thread Length: 1-11/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS90726170
Minimum Qty (MOQ):	15 EA
NSN:	5305-00-725-4138
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N MS90726-170 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	1.500 Inches Minimum And 1.688 Inches Maximum
Fastener Length:	3.500 Inches Nominal
Head Style:	Hexagon
Head Height:	0.378 Inches Minimum And 0.403 Inches Maximum
Width Between Flats:	0.922 Inches Minimum And 0.938 Inches Maximum
Nominal Thread Diameter:	0.625 Inches
Thread Quantity Per Inch:	18
Minimum Tensile Strength:	120000 Pounds Per Square Inch
Hardness Rating:	23.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Minimum Yield Strength:	85000 Pounds Per Square Inch
Material:	Steel Overall
Material Document And Classification:	Sae Gr 5 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS90726-170> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.