

Description

Fastener Length: 3", Thread: 1/4-28, Thread Length: 15/16

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS9072618
Minimum Qty (MOQ):	20
NSN:	5305-00-267-8962
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS90726-18 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.750 Inches Minimum And 0.938 Inches Maximum
Fastener Length:	3.000 Inches Nominal
Head Style:	Hexagon
Head Height:	0.150 Inches Minimum And 0.163 Inches Maximum
Width Between Flats:	0.428 Inches Minimum And 0.438 Inches Maximum
Nominal Thread Diameter:	0.250 Inches
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	150000 Pounds Per Square Inch
Hardness Rating:	32.0 Rockwell C Minimum Overall And 38.0 Rockwell C Maximum Overall
Minimum Yield Strength:	120000 Pounds Per Square Inch
Material:	Steel Overall
Material Document And Classification:	Sae Gr 8 Assn Std Single Material Response Overall
Surface Treatment:	Zinc Overall And Chromate Overall
Surface Treatment Document And Classification:	Astm B633 Ty 2 Sc 3 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unf

How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS90726-18> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.