

Description

Fastener Length: 2-3/4", Thread: 3/4-16, Thread Length: 1-15/16", MS90726 series bolt

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS90726190
Minimum Qty (MOQ):	5
NSN:	5305-00-727-8818
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS90726-190 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	1.750 Inches Minimum And 1.938 Inches Maximum
Fastener Length:	2.750 Inches Nominal
Head Style:	Hexagon
Head Height:	0.455 Inches Minimum And 0.483 Inches Maximum
Width Between Flats:	1.100 Inches Minimum And 1.125 Inches Maximum
Nominal Thread Diameter:	0.750 Inches
Thread Quantity Per Inch:	16
Minimum Tensile Strength:	120000 Pounds Per Square Inch
Hardness Rating:	23.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Minimum Yield Strength:	85000 Pounds Per Square Inch
Material:	Steel Overall
Material Document And Classification:	Sae Gr 5 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unf

How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS90726-190> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.