

P/N MS90726-36

Military-Fasteners.com

Description

Fastener Length: 1-1/4", Thread: 1/4-24, Thread Length: 7/8

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

| SKU / Model: | MS9072636 |
|-------------------------|---|
| Minimum Qty (MOQ): | 25 |
| NSN: | 5305-00-225-9091 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



P/N MS90726-36 Specifications

| Thread Class: | 2a |
|------------------------------|---|
| Thread Direction: | Right-hand |
| Thread Length: | 0.875 Inches Minimum |
| Fastener Length: | 1.250 Inches Nominal |
| Head Style: | Hexagon |
| Head Height: | 0.195 Inches Minimum And 0.211 Inches Maximum |
| Width Between Flats: | 0.489 Inches Minimum And 0.500 Inches Maximum |
| Nominal Thread Diameter: | 0.312 Inches |
| Thread Quantity Per Inch: | 24 |
| Minimum Tensile Strength: | 120000 Pounds Per Square Inch |
| Hardness Rating: | 23.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall |
| Material: | Steel Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Thread Series Designator: | Unf |
| Nondefinitive Spec/std Data: | 2 Type And 10p Style And 5 Grade |

How to Order

Order this machine bolt from our inventory online by visiting <u>https://military-fasteners.com/bolts/machine+bolts/MS90726-36</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.