

# P/N MS90726-38

# **Description**

Fastener Length: 1-1/2", Thread: 5/16-24, Thread Length: 63/64", MS90726 series screw

\* Manufacturer certifications are shipped with your order FREE of charge

# Order this part online

### **Additional Information**

SKU / Model: MS9072638

Minimum Qty (MOQ): 50

NSN: 5305-00-225-9093

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)







# P/N MS90726-38 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.875 Inches Minimum And 1.062 Inches Maximum
Fastener Length:	1.438 Inches Minimum And 1.500 Inches Maximum
Head Style:	Hexagon
Head Height:	0.195 Inches Minimum And 0.211 Inches Maximum
Width Between Flats:	0.489 Inches Minimum And 0.500 Inches Maximum
End Item Identification:	Generator, 30kw, Diesel, Military Standard Family; Support Equipment, B-52 Aircraft; Support Equipment, H-3 Helicopter; Truck, Fire/crash P2; Generator, 15kw, Diesel, Military Standard Family; Helicopter, Mh-53e; Chilled Water A/c Systems; Helicopter, Advance Attack, Ah-1w; Aircraft, Hx Unique; Close In Weapon System (ciws-phalanx)
Nominal Thread Diameter:	0.312 Inches
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	120000 Pounds Per Square Inch
Hardness Rating:	25.0 Rockwell C Minimum Overall And 34.0 Rockwell C Maximum Overall
Material:	Steel Comp 1013 Overall Or Steel Comp 1015 Overall Or Steel Comp 1016 Overall Or Steel Comp 1017 Overall Or Steel Comp 1018 Overall Or Steel Comp 1019 Overall Or Steel Comp 1020 Overall Or Steel Comp 1021 Overall Or Steel Comp 1022 Overall Or Steel Comp 1023 Overall Or Steel Comp 1025 Overall Or Steel Comp 1026 Overall Or Steel Comp 1029 Overall Or Steel Comp 1030 Overall Or Steel Comp 1033 Overall Or Steel Comp 1034 Overall Or Steel Comp 1035 Overall Or Steel Comp 1037 Overall Or Steel Comp 1038 Overall Or Steel Comp 1039 Overall Or Steel Comp 1040 Overall Or Steel Comp 1524 Overall Or Steel Comp 1527 Overall Or Steel Comp 1536 Overall Or Steel Comp 1541 Overall
Material Document And Classification:	Sae J429 Assn Std All Material Responses Overall
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2 Cl 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unf
Nondefinitive Spec/std Data:	2 Type And 10p Style And 5 Grade

# Order this hexagon head cap screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/hexagon+head+cap+screws/MS90726-38">https://military-fasteners.com/screws/hexagon+head+cap+screws/MS90726-38</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/screws/hexagon+head+cap+screws/MS90726-38">https://military-fasteners.com/screws/hexagon+head+cap+screws/MS90726-38</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/screws/hexagon+head+cap+screws/MS90726-38">https://military-fasteners.com/screws/hexagon+head+cap+screws/MS90726-38</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/screws/hexagon+head+cap+screws/MS90726-38">https://military-fasteners.com/screws/hexagon+head+cap+screws/MS90726-38</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/screws/hexagon-head+cap+screws/MS90726-38">https://military-fasteners.com/screws/hexagon+head+cap+screws/MS90726-38</a> and selecting the property of the selecting the selectin