

**Description**

Fastener Length: 1-3/4", Thread: 1/4-24, Thread Length: 0-63/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS9072639
Minimum Qty (MOQ):	45 EA
NSN:	5306-00-225-9094
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N MS90726-39 Specifications

<b>Thread Class:</b>	2a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.875 Inches Minimum And 1.062 Inches Maximum
<b>Fastener Length:</b>	1.688 Inches Minimum And 1.750 Inches Maximum
<b>Head Style:</b>	Hexagon
<b>Head Height:</b>	0.195 Inches Minimum And 0.211 Inches Maximum
<b>Width Between Flats:</b>	0.489 Inches Minimum And 0.500 Inches Maximum
<b>Nominal Thread Diameter:</b>	0.312 Inches
<b>Features Provided:</b>	Finished Head
<b>Thread Quantity Per Inch:</b>	24
<b>Minimum Tensile Strength:</b>	120000 Pounds Per Square Inch
<b>Hardness Rating:</b>	25.0 Rockwell C Minimum Overall And 34.0 Rockwell C Maximum Overall
<b>Material:</b>	Steel Overall
<b>Material Document And Classification:</b>	Sae Gr 5 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses Overall
<b>Thread Series Designator:</b>	Unf

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS90726-39> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.